



KOHLER OILS AND LUBRICANTS

TECHNICAL DATA SHEET

KOHLER ATF DEX II

Automatic Transmission Fluid

Product Specification & Description

Specification: ATF 3309- Multi-Vehicle

Description: Kohler ATF DEX II is a high performance oil for use in most automatic transmission units and power steering units.

Applications

KOHLER ATF DEX II is recommended for use in power steering units and most automatic transmission units of vehicles requiring Mercon or Dexron IID performance.

Key Performance Features

Kohler ATF DEX II is a high performance oil formulated from select additives and base oils and offer excellent anti-wear and oxidation control properties as well as “non-chatter” operation as a result of friction modifier additives. It is easy to use due to excellent filterability and performs outstandingly in low temperatures.

Typical Characteristics

Viscosity, cSt at 40°C	41.60
Viscosity, cSt at 100°C	7.60
Viscosity Index	152
Density, kg/m ³ at 15°C	860
Pour Point, °C	-38
Flash Point, °C	185

***The range of values of the specifications shown in the table above are typical values given as an indication only.



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER ATF DEX II

Automatic Transmission Fluid

Storage and Handling

Avoid temperatures above 60°C and exposure to strong sunlight. Use oil resistant gloves and PPE when handling product to avoid skin contact. Safety goggles must be worn if eye contact is a potential concern. This product should be used for its intended purpose only. When disposing make sure local regulations are complied with. Avoid contaminating soil or drainage into bodies of water or sewage.

Pack Sizes

- 500mL, 1L, 5L and 20L Plastic Bottles
- 200L Steel Drums