



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER FULLY SYNTHETIC 5W30

Product Specification & Description

Specification: API SN/CF, ACEA A3/B4

Description: Kohler Fully Synthetic 5W-30 engine oil is a high performance oil, incorporating synthetic technology for petrol, diesel, passenger and light commercial vehicles as per manufacturer's requirements.

Key Performance Features

- Recommended for high performance vehicles.
- Extended oil drain intervals
- Excellent detergent properties giving longer engine life
- High viscosity index resulting in stable viscosities
- Enhanced anti-wear properties
- Good cold start up and excellent lubrication in extreme temperatures.

Typical Characteristics

SAE No.	5W-30
Viscosity, cSt at 40°C	79.90
Viscosity, cSt at 100°C	12.30
Viscosity Index	>151
Density, kg/m ³ at 15°C	850
Pour Point, °C	-40
Flash Point, °C	246
Total Base Number, mgKOH/g	6.1

***The range of values of the specifications shown in the table above are typical values given as an indication only.

Storage and Handling

Avoid temperatures above 70°C and exposure to strong sunlight. Use oil resistant gloves and PPE when handling product to avoid skin contact. Safety goggles must be worn if eye contact is a potential concern. This



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER FULLY SYNTHETIC 5W30

product should be used for its intended purpose only. When disposing make sure local regulations are complied with.

Pack Sizes

- 500mL, 1L, 5L and 20L Plastic Bottles
- 200L Steel Drums