



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER ENGINE OIL 20W50

Product Specification & Description

Specification: API SL/CF

Description: Kohler 20W-50 Multigrade engine oil is a high performance lubricant designed for internal combustion engines for increased engine life and reduced ring and bearing wear.

Key Performance Features

- Excellent anti-sludge properties
- Excellent anti-oxidant
- Good fuel economy
- Excellent soot handling
- Reduced bearing and ring wear

Typical Characteristics

SAE No.	20W-50
Viscosity, cSt at 40°C	170.30
Viscosity, cSt at 100°C	19
Viscosity Index	>127
Density, kg/m ³ at 20°C	890
Pour Point, °C	-21
Flash Point, °C	230
Total Base Number, mgKOH/g	7.5

***The range of values of the specifications shown in the table above are typical values given as an indication only.

Storage and Handling

Avoid temperatures above 60°C and exposure to strong sunlight. Use oil resistant gloves and PPE when handling product to avoid skin contact. Safety goggles must be worn if eye contact is a potential concern. This



KOHLER OILS AND LUBRICANTS

TECHNICAL DATA SHEET

KOHLER ENGINE OIL 20W50

product should be used for its intended purpose only. When disposing make sure local regulations are complied with.

Pack Sizes

- 500mL, 1L, 5L and 20L Plastic Bottles
- 200L Steel Drums