



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER GEAR OIL 80W90

Product Specification & Description

Specification: API GL-5

Description: Kohler 80W-90 GL-5 is a high performance gear oil formulated from select additives and base oils for use in limited slip differentials, lubrication of axles, gearboxes and mechanical steering controls.

Key Performance Features

Slik X 80W-90 GL-4 is a high performance gear oil formulated from select additives and base oils and offer excellent anti-wear properties as well as “non-chatter” operation as a result of the friction modifier additives.

Typical Characteristics

SAE No.	80W-90
Viscosity, cSt at 40°C	129
Viscosity, cSt at 100°C	14.10
Viscosity Index	107
Pour Point, °C	-18

***The range of values of the specifications shown in the table above are typical values given as an indication only.

Storage and Handling

Avoid temperatures above 70°C and exposure to strong sunlight. Use oil resistant gloves and PPE when handling product to avoid skin contact. Safety goggles must be worn if eye contact is a potential concern. This product should be used for its intended purpose only. When disposing make sure local regulations are complied with. Avoid contaminating soil or drainage into bodies of water or sewage.

Pack Sizes

- 500mL, 1L, 5L and 20L Plastic Bottles
- 200L Steel Drums