



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER PART SYNTHETIC 5W40 ENGINE OIL

Product Specification & Description

Specification: API SN/CF- A3/B4

Description: Kohler Part Synthetic 5W-40 is a high performance lubricant using a mixture of mineral and synthetic base oils in the formulation. Suitable for passenger and light commercial motor vehicles.

Applications

Recommended for use in petrol and diesel engines. Suitable for most severe operating conditions in extreme weathers.

Key Performance Features

- Excellent detergent properties giving longer engine life
- High viscosity index resulting in stable viscosities
- Enhanced anti-wear properties

Typical Characteristics

SAE No.	5W-40
Viscosity, cSt at 40°C	87.30
Viscosity, cSt at 100°C	13.40
Viscosity Index	155
Density, kg/m ³ at 20°C	850
Pour Point, °C	-40
Flash Point, °C	236
Total Base Number, mgKOH/g	8.7

***The range of values of the specifications shown in the table above are typical values given as an indication only.



TECHNICAL DATA SHEET

KOHLER OILS AND LUBRICANTS

KOHLER PART SYNTHETIC 5W40 ENGINE OIL

Storage and Handling

Avoid temperatures above 70°C and exposure to strong sunlight. Use oil resistant gloves and PPE when handling product to avoid skin contact. Safety goggles must be worn if eye contact is a potential concern. This product should be used for its intended purpose only. When disposing make sure local regulations are complied with.

Pack Sizes

- 500mL, 1L, 5L and 20L Plastic Bottles
- 200L Steel Drums